INOX | Upright Cabinets

REFRIGERATED CABINETS ► GN2/1-NO FROST ► CHILLER



















DETAILS







Evaporator with anti-corrosion treatment



Inner stainless steel waved guides



Anti-condensation Lock fitted as "thermal-braker" on standard door frame





Digital control and white backlit main switch



Inner LED light



Cabinet suitable for GN2/1 pans



Triple temperate glass with grey silk

GENERAL FEATURES

| GN2/1 Refrigerated upright cabinet (GLASS DOOR) | • |
|--|---|
| Stainless Steel exterior and interior | • |
| Plastic thermal-braker anti-condensation as chamber body frame | • |
| Ventilated Cooling | • |
| Evaporator with anti-corrosion treatment | • |
| Hot gas defrost system | • |
| Foaming Agent Cyclopentane (80mm) | • |
| Curved edge for easy cleaning | • |
| Digital Thermostat | • |
| White backlit main switch | • |
| LED light and lock fitted as standard | • |
| Removable Gasket | • |
| Door with self closing (Not reversable) | • |
| Foamed door handle | • |
| Adjustable shelves GN2/1: 3 + 1 | • |
| N.4 S/S Adjustable feet - (Lockable castor as Optional) | • |
| Energy efficiency class: E | • |

TECHNICAL SPECIFICATIONS

| Capacity | 546 L |
|----------------------------------|--------------|
| Temperature | +3° ~ +10°C |
| Consumption | 2.38 kWh/24h |
| Rated Power | 311 W |
| Noise level | 50 dB(A) |
| Net Weight | 114.50 Kg |
| Gross Weight | 133.00 Kg |
| External Dimensions (WxDxH mm) | 700x891x2045 |
| Internal Dimensions (WxDxH mm) | 534x685x1485 |
| Packaging dimensions (WxDxH mm) | 720x860x2110 |
| Loading quantities 20'/40'/40'HQ | 21/43/43 |
| | |

CERTIFICATION

(E C



RoHS

PRODUCT DIMENSIONS







